



Cixi Weillite Sealing Material Co., Ltd

WLT- 001A Flexible Graphite Sheet with tanged 0.1mm SS316 inserted

Graphite sheet + 0.10mm Tanged SS316 + Graphite sheet

Introduction

WLT- 001A Reinforced Graphite composite Sheet is made from flexible graphite sheet reinforced with a single insertion of tanged 0.10 mm thick 316 stainless steel. No adhesive is required to bond the graphite layers as the graphite material is fixed to the insert by small, sharp teeth, resulting in a sturdy gasket material which is relatively easy to process and handle.

Applications

This product is used frequently in flange connections for piping and machinery. Its wide temperature range and excellent stress retention make it extremely suitable for use in steam systems, in the chemical and petrochemical industries, processing industry, etc. Reinforced Graphite composite Sheet is mainly used for making cylinder gaskets of engines and punching into all kinds of sealing gaskets.

Technical data

Property	Standard	value
Thickness mm		1.0 to 3.0
Density(graphite sheet) g/cm ³		1.0
Temperature °C	In oxidizing media	-200°C to +550°C
Max. pressure bar		140
Sulphur content ppm		<1500
Chloride content ppm		<50
Compressibility %	ASTM F36A-66	30-40
Recovery %	ASTM F36A-66	≥15

Standard Size

Length: 1000mm, 1500mm

Width: 1000mm, 1500mm

Thickness: 1.0mm to 3.0mm

Add: West Factory Area, No.669 QingShaoNianGong North Road, Economic Development Zone, Cixi City, Zhejiang, China

Tel: 86-574-63037810

Fax: 86-574-63037820

URL: <http://www.gasketsheet.com>

Email: sales@gasketsheet.com